



Steatite connection blocks 450V range



Protected against accidental electric contact,
brass terminals, nickel plated steel screws.



4mm²

BU041	7 gr.	SOLID CONDUCTOR	BU042	13 gr.
		<p>5.5-6.5 mm 4mm² / 2.5mm² / 1.5mm² AWG12 / AWG14 / AWG16</p> <p>STRANDED CONDUCTOR</p> <p>5.5-6.5 mm 4mm² / 2.5mm² / 1.5mm² AWG12 / AWG14 / AWG16</p>		
BU043	20 gr.	<p>0.4 N.m</p> <p>450V</p> <p>Permanent 230°C / 450°F Peak 450°C / 840°F</p>	BU044	26 gr.
	<p>M2.6</p> <p>32A</p>			

6mm²

BU061	9 gr.	SOLID CONDUCTOR	BU062	15 gr.
		<p>5.5-7.5 mm 6mm² / 4mm² / 2.5mm² AWG10 / AWG12 / AWG14</p> <p>STRANDED CONDUCTOR</p> <p>5.5-7.5 mm 4mm² / 2.5mm² AWG12 / AWG14</p>		
BU063	25 gr.	<p>0.5 N.m</p> <p>450V</p> <p>Permanent 230°C / 450°F Peak 450°C / 840°F</p>	BU064	35 gr.
	<p>M3</p> <p>41A</p>			



Page (.pdf)



Drawing 2D (.dwg)



Drawing 3D (.stp)